

Breakers

More power, less vibration, even quieter



AH 182

H 92

- Cast, galvanised stainless steel grip
- User-friendly, powerful and reliable
- Exceptional performance with low compressed air demand, soundproofing and minimal vibration
- Vibration-dampening as standard from 20 kg
- Grip vibration suppression for optimum kick-back protection

	Model	Blow frequency per min	Air demand *) m ³ /min	Chuck – Shank	Weight kg	Impact force Nm	Weighted sum acceleration value **) m/s ²
Grip	H 62	2430	1.1	S 19 x 50 a)	5.8	13.5	7.5
	H 92	1690	1.2	Ø R 25 x 75 b)	9.3	34	6.2
	H 92	1690	1.2	S 22 x 82.5 c)	9.5	34	6.2
	H 92	1690	1.2	S 22 x 82.5 d)	9.8	34	6.2
	H 111	1560	1.4	Ø R 25 x 75 a)	12.0	40	7.7
	H 111	1560	1.4	S 22 x 82.5 c)	12.5	40	7.7
	H 131	1175	1.5	S 22 x 82.5 d)	15.4	53	9.2
Grip Vibration damped	H 92 V	1760	1.3	S 22 x 82.5 c)	10.6	30	1.8
	H 111 V	1625	1.5	S 22 x 82.5 c)	12.8	40	5.1
	H 131 V	1135	1.2	S 22 x 82.5 c)	13.9	53	5.0
T-grip Vibration damped	AH 182 V	1305	1.6	S 25 x 108 e)	20.1	49	6.6
	AH 211 V	1175	1.7	S 25 x 108 e)	21.2	58	5.2
	AH 251 V	1065	1.7	S 28 x 152 e)	24.6	64	6.5
	AH 251 V	1065	1.7	S 32 x 152 e)	24.4	64	6.5
	AH 301 V	1095	1.9	S 32 x 152 e)	27.5	74	8.9

*) at 6 bar **) as per ISO8662 a) = Retaining spring b) = Retaining cap c) = Cross-head cap d) = Retaining pin e) = Locking retaining cap



KAESER KOMPRESSOREN GmbH

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel: +49 9561 640-0 – Fax: +49 9561 640130
www.kaeser.com – e-mail: productinfo@kaeser.com