

ECONOMY-Breakers

Ergonomic design, maximum power



- Ergonomic design for comfort and ease of use
- Compact, handy construction

	Model	Blow frequency per min	Air demand *) m ³ /min	Chuck – Shank		Weight kg	Impact force Nm	Weighted sum accelera- tion value**) m/s ²
Handle	CH 0	3600	0.4	15.0 x 12.8 x 55.0	a)	2.6	7	12.0
	H 31	2800	0.5	17.5 x 14.8 x 60.0	a)	4.5	12	10.0
	CH 3	2400	0.7	17.5 x 14.8 x 60.0	a)	5.8	12	10.6
	CHH 4	1800	1.0	17.5 x 14.8 x 60.0	b)	8.1	29	11.6
	H 10	1300	0.9	S 22 x 82.5	c)	9.5	7	16.0
T-grip	AH 152	1600	1.1	S 25 x 108	c)	18.0	11	18.6
	AH 201	1030	1.3	S 25 x 108	c)	20.0	13	15.5
	AH 28	1100	1.7	S 32 x 152	c)	28.0	17	13.8

*) at 6 bar **) as per ISO8662 a) = Retaining spring b) = Retaining cap c) = Cross-head cap d) = Retaining pin e) = Locking retaining catch f) = Retaining clip
Appropriate tools are available separately: pointed chisel, flat chisel, scaling chisel, spader