

Hammer drills – Exceptional performance

**Power through
concrete + stone**



- Optimum drilling performance
- Robust design and galvanised surfaces ensure long service life
- Grip, cylinder and casings are made from cast stainless steel
- Air buffer minimises component wear during standby operation
- From model BH 11 available with power blowing system for blowing out the drill hole

	Model	Blow frequency	Air demand *)	Chuck – Shank		Weight kg	Impact force Nm	Weighted sum acceleration value **) m/s ²
		per min	m ³ /min					
Grip	BH 8	3240	0.6	○ S19 x 82.5	a)	8.6	10	13.1
	BH 8	3240	0.6	○ S22 x 82.5	a)	8.6	10	13.1
	BH 11	2400	1.4	○ S22 x 108	b)	15.5	24	20.0
T-grip	BH 16	2400	1.8	○ S22 x 108	b)	18.9	31	20.3
	BH 21	2540	1.7	○ S22 x 108	b)	22.8	40	23.1
T-grip (vibration damped)	BH 16 V	2040	1.6	○ S22 x 108	b)	22.9	31	4.8

*) at 5 bar **) As per ISO8662 a) = Retaining spring b) = Retaining cap

Applicable drill sets are available separately: mono-block drill, chuck, drill bit



KAESER Kompressoren GmbH

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel: +49 9561 640-0 – Fax: +49 9561 640130
www.kaeser.com – e-mail: productinfo@kaeser.com